

Kebony Clear Decking w side slits 22 x 142

Product Description

Kebony Clear products are produced from FSC® certified Radiata Pine modified with a bio-based liquid.


The patented Kebony technology permanently alters the wood cell structure to give a unique wood product with outstanding durability and no maintenance needs beyond normal cleaning.

Kebony Clear products have a primarily clear front surface and are treated through the board.



Quality and Appearance upon delivery

Profile	Rectangular with smooth surface
Dimension	22 x 142
Standard Length(s)	3,0 - 3,6 - 4,2 - 4,8 m. For availability and possible alternative lengths please contact your Kebony representative or our local Kebony trade partner.
End-treatment	Straight
Finish	Satin
Knots/Pitch pockets	3 sides clear
Cupping	No limitation
Crook	
Moisture	4-5 %
Cracks	Surface cracks visible, but not continuous
Wane	Max. 1/3 of thickness and width
NOTE	There may be defects on the back side. These will not affect the technical quality of the product.



The Kebony technology gives the wood a deep rich brown colour (some natural colour variations will occur and there are possible darker areas as a result of the process). After exposure to sun and rain the wood will develop a natural silver-gray patina where surface cracks and checks may appear, this is a natural development and will not influence the performance and durability of the wood.

Technical data (average values)

	Kebony	Untreated	
Density (12 % mc)	637	480	Kg/m ³
Hardness (EN 1534)	4,1	2.5	Brinell
Max swelling (dry to wet, tangential direction)	4	8	%
Decay resistance (EN 350)	1-2**	5	Durability class 1-5
Use class (EN 335)	3***	1	

* Suitable for outdoor applications above ground

Certifications

FSC CU-COC-813689 - www.fsc.org
 Nordic Ecolabel 2086 0001 - www.nordic-ecolabel.org
 EPD: NEPD-407-287-EN - www.epd-norge.no
 CE marked according to EN 14915
 Complies with EU Timber Regulation (EUTR)
 AbZ
 Kebony installation guide for decking - www.kebony.com



Environment

Kebony products are exempted from the EU's biocide directive (76/769/EEC)

Waste handling as ordinary wood.

Disclaimer

Up to 5% of the delivered boards may be outside this specification and must be accepted.

Kebony products will change in appearance when exposed to rain and sun. Colour changes and surface cracks will occur due to natural weathering. The manufacturer cannot be held liable for any such variations in colour and surface appearance. This will not influence durability and overall performance of the product.

This data sheet applies for the original profile - any alterations may influence the technical performance of the product.

Kebony is continuously working on product development. Information in this datasheet may be changed without further notice.