

2653 - Kebony Clear rough sawn 50 x 125

Kebony Clear products are produced from FSC® certified Radiata Pine modified with a bio-based liquid.

The patented Kebony technology permanently alters the wood cell structure to give a unique wood product with outstanding durability and no maintenance needs beyond normal cleaning.

Kebony Clear products have a primarily clear front surface and are treated through the board.



Quality and Technical data

Profile	Rough	Density (12 % mc)	670	Kg/m3
Dimension	50 x 125	Hardness (EN 1534) Brinell	42	MPa
Weight	4.19 Kg/lm			
		Max swelling (dry to wet, tangential direction)	4	%
		Decay resistance (EN 350)	1	Durability class 1-5
		Use class (EN 335)	3.2*	
Knots/Pitch pockets	No knots	Fire Class Untreated		
Cupping	Max 1% of width			
Crook	3-3,6 m: max 10 mm; 4,2-4,8 m: max 13 mm			
Moisture	4-8 %			
Cracks	Surface cracks and checks may be visible			
Wane	May occur on the back			

There may be defects on the back side. These will not affect the technical quality of the product.

* Installed as per Kebony installation guidelines;** Not suitable for outdoor applications

Weathered



Certifications

FSC
CU-COC-813689



The mark of
responsible forestry

SWAN
2086 001



Environment

Kebony products are exempted from the EU's biocide directive (76/769/EEC)
Waste handling as ordinary wood.

Disclaimer

Please refer to our Terms and Conditions available on our website for detailed information.